

ETHERNET JACKS WITH INTEGRATED MAGNETICS AND PoE

Ethernet jacks with integrated magnetics and Power over Ethernet (PoE) from TE Connectivity (TE) offer a highly integrated connectivity PCB solution for Industrial Ethernet applications. Using a 3-wire choke improves EMI performance and allows for remote powering of peripherals over the Ethernet cable. The new jacks comply to the IEEE 802.3at (PoE+) standard, which supports up to 25.5W of power per ports. The Ethernet jacks support an industrial temperature range and can be used in reflow soldering production processes at 260°C for easy and cost effective manufacturing. All features combined with high corrosion resistivity makes the new series of jacks extremely suited for a broad spectrum of industrial applications.

BENEFITS

- Supporting 260°C reflow solder processes to simplify manufacturing without extra process step
- Reduction of electrical problems and corrosion via thicker plating
- Fits Industrial applications: -40°C to +85°C temp range
- Compact design on PCB using integrated magnetics
- Remote powering supported by 802.3at PoE
- Enhanced EMI with 3 wire choke

APPLICATIONS

- Industrial Communications & Ethernet
- Industrial Machinery
- Industrial Production Equipment
- Automated Test Equipment

FEATURES

- Extended temperature range -40°C to +85°C
- PoE+ support according to 802.3at
- Plating thickness 0.76µm [30µ inch] Gold over 1.27µm [50µ inch] Nickel

MATERIALS

- Plating thickness 0.76µm [30µ inch] Gold over 1.27µm [50µ inch] Nickel
- High grade LCP
- UL94-V0
- 260°C reflow capable
- Moisture sensitivity level (MSL) 1

ELECTRICAL

- 10/100 Mbps Ethernet, 1 Gbps
- Dielectric withstanding 2250V DC
- Supports voltage or current mode applications
- 3-wire choke

MECHANICAL

- -40°C to +85°C
- Min. 750 mating cycles
- Different configurations available
















STANDARDS & SPECIFICATIONS

- Product Specification: 108-94694
- Application Specification: 114-94556

Ethernet Jacks with Integrated Magnetics and POE

https://cwindustrial.co.za/

PRODUCT OFFERINGS

Part Number	Description	Speed	Ports	Orientation	Tab	LEDs	Packaging	Solder Pin and Shield Length [mm]	
2337992-3	RJ45 JACK MAG. PoE 10/100 LED 1x1 INV.	10/100	1x1	R/A	Up	Yes	T&R	1,9	
2337992-4	RJ45 JACK MAG. PoE 10/100 LED 1x1	10/100	1x1	R/A	Down	Yes	T&R	1,9	
2337992-5	RJ45 JACK MAG. PoE 1Gb LED 1x1 INV.	1G	1x1	R/A	Up	Yes	T&R	1,9	
2337992-8	RJ45 JACK MAG. PoE 1Gb LED 1x1	1G	1x1	R/A	Down	Yes	T&R	1,9	
2337993-2	RJ45 JACK MAG. PoE 10/100 LED 1x1 VERT.	10/100	1x1	Vertical	-	Yes	T&R	1,9	
2337994-3	RJ45 JACK MAG. PoE 10/100 LED 1x2 INV.	10/100	1x2	R/A	Up	Yes	T&R	1,9	
2337994-4	RJ45 JACK MAG. PoE 10/100 LED 1x2	10/100	1x2	R/A	Down	Yes	T&R	1,9	
5-2337992-3	RJ45 JACK MAG. PoE 10/100 LED 1x1 INV.	10/100	1x1	R/A	Up	Yes	Tray	1,9	
5-2337992-4	RJ45 JACK MAG. PoE 10/100 LED 1x1	10/100	1x1	R/A	Down	Yes	Tray	1,9	
5-2337992-5	RJ45 JACK MAG. PoE 1Gb LED 1x1 INV.	1G	1x1	R/A	Up	Yes	Tray	1,9	
5-2337992-8	RJ45 JACK MAG. PoE 1Gb LED 1x1	1G	1x1	R/A	Down	Yes	Tray	1,9	
5-2337993-2	RJ45 JACK MAG. PoE 10/100 LED 1x1 VERT.	10/100	1x1	Vertical	-	Yes	Tray	1,9	
5-2337994-3	RJ45 JACK MAG. PoE 10/100 LED 1x2 INV.	10/100	1x2	R/A	Up	Yes	Tray	1,9	
5-2337994-4	RJ45 JACK MAG. PoE 10/100 LED 1x2	10/100	1x2	R/A	Down	Yes	Tray	1,9	
5-2337995-1	RJ45 JACK MAG. PoE 10/100 LED 2x1	10/100	2x1	R/A	Down	Yes	Tray	1,9	

Industrial RJ45 also offers integrated magnetics and discrete series (X-2301994-X; X-2301995-X; X-2301996-X; X-2301997-X), please go to [te.com](#) for details

Authorized Distributor of TE Connectivity